

Applications

- 2.4 GHz ISMband
- IEEE 802.11b/g wirelessLAN
- Wi-Finetworks
- 2.4 GHz wireless videosystems
- Multipoint and mobileapplications

Features

- Compact size, only 110mm long
- Flexible Rubber Duck antenna
- Tilt and swivel design
- Multiple connector options
- Optional magnetic mounts available

Description


This compact 2.4 GHz Omni-directional rubber duck antenna provides broad coverage and 3 dBi gain. It is a coaxial sleeve design with an Omni-directional pattern. It is ideally suited for IEEE 802.11b/g wireless LAN and other Wi-Fi applications.




2.4 GHz 3 dBi Rubber Duck Antenna Model:SRFS 2400/2500 3A/RD

TECHNICAL SPECIFICATIONS	
Frequency Range	2400 ~ 2500 MHz
Gain	3 dBi
V.S.W.R	<2.0
Polarization	Vertical
Impedance	50 Ω
Lightning Protection	Direct Ground
Maximum Input Power	50 W
Directional	Omni
MECHANICAL SPECIFICATION	
Radome Material	Plastic
Connector	SMA M or Customized
Antenna Length	110 mm
Color	Black
Humidity	5~95%
Operating Temperature (°C)	-40°C ~ 85°C
Environmental Friendly	ROHS Compliant

RF Antenna Patterns



Vertical



Horizontal