



7/8" Hansen Feeder Cable
Part No. RF50 7/8"

- The high Performance of attenuation allows co-axial cable to be used in different RF systems , such as 3G, 4G Mobile Communication.
- Wide range of applications, such as indoor distribution, broadcast, various base stations wireless cellular, and others.
- Lower VSWR, perfect shielding effectiveness, and extraordinary inter-modulation performance lead to fewer energy loss and outer interference

Construction		Diameter
Inner Conductor	Copper Tube	8.70 mm
Insulation	Physically Foamed PE	22.50 mm
Outer Conductor	Ring Corrugated Copper	24.90 mm
Jacket	PE	27.30 mm

Electrical Characteristics	
Impedance	50Ω
Cut-off Frequency	DC – 5.5 GHz
Nominal Capacitance	75 p F/m
Nominal Inductance	0.19 μ H/m
Velocity of Propagation	86%
DC Breakdown Voltage	6.0kV
PIM	≤ -160 dBc@ (2x20W)
Peak Power Rating	91.0 kW
Insulation Resistance	> 5 x 10 ³ MΩ / Km
Screening Attenuation	>120 dB

Mechanical & Environmental Specification	
Min. Single Bending Radius	120 mm
Min. Repeated Bending Radius	250 mm
Max. Tensile Force	1470 N
Recommended Maximum Clamp Spacing	1 m
Storage Temperature	-55to +80°C
Installation Temperature	-40 to +60°C
Operating Temperature	-55 to +80°C
RoHS	Compliant

Frequency (MHz)	Attenuation & Average Power at 20°C	
	dB/100 m (dB/100ft)	kw
100	1.19 (0.36)	7.56
450	2.65 (0.81)	3.41
690	3.35 (1.02)	2.85
800	3.63 (1.11)	2.48
900	3.88 (1.18)	2.33
1000	4.12 (1.26)	2.19
1800	5.75 (1.75)	1.57
2000	6.11 (1.86)	1.48
2200	6.45 (1.97)	1.41
2400	6.79 (2.07)	1.34
2500	6.95(2.12)	1.30
2600	7.12(2.17)	1.27
2700	7.28(2.22)	1.25
3000	7.76(2.37)	1.16

VSWR	
800 ~ 1000 MHz	1.12
1700 ~ 2200 MHz	1.12
2300 ~ 2400 MHz	1.12
2500 ~ 2700 MHz	1.15